

## Technical / Safety Data Sheet GRP-Specialist Sheet Products

- DESCRIPTION -Cured polyester resin reinforced with Fibreglass chopped strand mat.
- 2. **CLASSIFICATION** -Not classified (non hazardous).
- 3. **FLAMMABILITY** -Flash point N/A. Extinguishing media water, foam, C02, dry powder.
- 4. **HEALTH & STORAGE** -No hazard in normal use. Nuisance dust hazard when cutting and grinding (irritation to mouth, nose, throat and skin).
- 5. **HANDLING & STORAGE** -Possibility to static discharge when handling multiple sheets, possibility of minor cuts from exposed edges.
- 6. **RECOMMENDATION** -Flat sheets should be stored flat to avoid warpage. Flat sheets should be carried vertical to avoid sag. Heavy duty rubber gloves should be worn for handling to reduce problems of static and cuts. Good workshop practice should be observed when cutting and grinding. Advice should be sought from ventilation / extraction companies. Wear eye protection and dust masks if appropriate when cutting etc.
- 7. **DISPOSAL** -Dispose in accordance with local regulations. Primary method of disposal is in municipal or industrial landfill.
- 8. **SPECIAL PRECAUTIONS** -Advice should sought from SCANDIC COATING SWEDEN prior to its products being used in food preparation areas or if they are used in the manufacture of toys.
- LIABILITY -Information contained in the publication is accurate to the best of our knowledge. SCANDIC COATING SWEDEN and/or its subsidiary companies do not accept liability arising out of the use of this information or the use, application, adaptation or processing of the products so desired.
- 10. Remove all film before installation or one week after delivery.
- 11. Keep panels flat where possible.
- 12. Graffiti can be removed using standard solvents without the fear of smudging or permanently marking the panel. Dirt and grime build up can be removed using hot soapy water then dried with a clean cloth to remove any soap streaks.

Scandic Coating Sweden - Johanneslustgatan 1 - 212 28 Malmo - Sweden Ph.: +46 - 4029 2859 Mobile: +46 708 80 55 66

Web: www.scandic-coating.com - Email: info@Scandic-coating.com